

Declaration of performance

No. 6 - 528/108/37 (Valid from 01.05.2020)

E: INFO@PETERSEN-TEGL.DK
P: +45 7444 1236
W: PETERSEN-TEGL.DK

1. **Unique identification code of the product type:** K11-K21-K22-K23-K36-K50-K54-K70-K71-K91-K92-K96-K97-K363
2. **Intended use/es:** U unit for use in unprotected masonry
3. **Manufacturer:** Petersen Tegl A/S, Nybølnorvej 14, DK-6310 Broager
4. **Authorized representative:** Not applicable
5. **System/s of AVPC:** System 2+
6. **Harmonized standard:** EN 771-1:2011+A1:2015
- Notified body/ies:** NB 1073
7. **Declared performance/s:**

Essential Characteristics			Performance
Dimensions	Length/width/height (mm)		528/108/37
Dimensional tolerances	Mean value		Tm (10/4/3 mm)
	Range		NPD*
Configuration	Group according to EN 1996-1-1, table 3.1		G1
Compressive strength	Category		1
	Mean value		≥30 N/mm2
	Normalised		NPD*
	Direction of load		Parallel to the bed surface
Dimensional stability	Moisture movement		NPD*
Bond strength (according to EN 998-2, Appendix C)			NPD*
Active soluble salts content			S2
Reaction to fire			A1
Water absorption			NPD*
Water vapour permeability			NPD*
Direct airborne sound insulation	Gross dry density	Mean value	NPD*
		Tolerance	NPD*
Thermal resistance			NPD*
Durability against freeze/thaw			F2
Dangerous substances			NPD*

* No performance determined

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Broager, 01.05.2020


CFO Poul M. Kjeldsen



NB 1073

Petersen Tegl A/S, Nybølnorvej 14, DK-6310 Broager

17

Declaration of performance No. 6 - 528/108/37 (Valid from 01.05.2020)

EN 771-1:2011+A1:2015

K11-K21-K22-K23-K36-K50-K54-K70-K71-K91-K92-K96-K97-K363

U unit for use in unprotected masonry

Category 1

Dimensions	Length/width/height (mm)		528/108/37
Dimensional tolerances	Mean value		Tm (10/4/3 mm)
	Range		NPD*
Configuration	Group according to EN 1996-1-1, table 3.1		G1
Compressive strength	Category		1
	Mean value		≥30 N/mm2
	Normalised		NPD*
	Direction of load		Parallel to the bed surface
Dimensional stability			NPD*
Bond strength (according to EN 998-2, Appendix C)			NPD*
Active soluble salts content			S2
Reaction to fire			A1
Water absorption			NPD*
Water vapour permeability			NPD*
Direct airborne sound insulation	Gross dry density	Mean value	NPD*
		Tolerance	NPD*
Thermal resistance			NPD*
Durability against freeze/thaw			F2
Dangerous substances			NPD*

* No performance determined

UK Declaration of performance

No. UK6 - 528/108/37 (Valid from 22.08.2022)

Certificate Number: 0086-CPR-766512

E: INFO@PETERSEN-TEGL.DK
P: +45 7444 1236
W: PETERSEN-TEGL.DK

1. **Unique identification code of the product type:** K11-K21-K22-K23-K36-K50-K54-K70-K71-K91-K92-K96-K97-K363
2. **Intended use/es:** U unit for use in unprotected masonry
3. **Manufacturer:** Petersen Tegl A/S, Nybølnorvej 14, DK-6310 Broager
4. **Authorized representative:** Not applicable
5. **System of assessment and verification of constancy of performance of the construction product:** System 2+
6. **UK designated standard:** BS EN 771-1:2011+A1:2015
UK approved body: 0086 (BSI Assurance UK Ltd)

7. **Declared performance:**

Essential Characteristics			Performance
Dimensions	Length/width/height (mm)		528/108/37
Dimensional tolerances	Mean value		Tm (10/4/3 mm)
	Range		NPD*
Configuration	Group according to EN 1996-1-1, table 3.1		G1
Compressive strength	Category		1
	Mean value		≥30 N/mm2
	Normalised		NPD*
	Direction of load		Parallel to the bed surface
Dimensional stability	Moisture movement		NPD*
Bond strength (according to EN 998-2, Appendix C)			NPD*
Active soluble salts content			S2
Reaction to fire			A1
Water absorption			NPD*
Water vapour permeability			NPD*
Direct airborne sound insulation	Gross dry density	Mean value	NPD*
		Tolerance	NPD*
Thermal resistance			NPD*
Durability against freeze/thaw			F2
Dangerous substances			NPD*

* No performance determined

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with UK legislation Construction Products Regulations 2019 No. 465, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Broager, 22.08.2022


CFO Poul M. Kjeldsen

UK CA 0086 (BSI Assurance UK Ltd) Petersen Tegl A/S, NybølNorvej 14, DK-6310 Broager 22			
BS EN 771-1:2011+A1:2015			
K11-K21-K22-K23-K36-K50-K54-K70-K71-K91-K92-K96-K97-K363			
U unit for use in unprotected masonry			
Category 1			
Dimensions	Length/width/height (mm)		528/108/37
Dimensional tolerances	Mean value		Tm (10/4/3 mm)
	Range		NPD*
Configuration	Group according to EN 1996-1-1, table 3.1		G1
Compressive strength	Category		1
	Mean value		≥30 N/mm2
	Normalised		NPD*
	Direction of load		Parallel to the bed surface
Dimensional stability			NPD*
Bond strength (according to EN 998-2, Appendix C)			NPD*
Active soluble salts content			S2
Reaction to fire			A1
Water absorption			NPD*
Water vapour permeability			NPD*
Direct airborne sound insulation	Gross dry density	Mean value	NPD*
		Tolerance	NPD*
Thermal resistance			NPD*
Durability against freeze/thaw			F2
Dangerous substances			NPD*

* No performance determined